



Technical Data Sheet

U-E20-FLEX – Damper 2 mm for U-TOP-FLEX

COMPONENTS

The U-E20-FLEX is composed of 1 piece.

CHARACTERISTICS

Diameter: ø 175 mm Thickness: 2 mm

MATERIAL

Material: SBR

Hardness Shore A DIN 53505: 60-80 SHA

Color: Black

Density: 1.55 g/cm³

Temperature range:-30°C to +/- 70 °C Tensile Strenght DIN 53504: 3 Mpa Elongation at break DIN 53504: 250%


Resistant to weathering, sea salts, algae and a wide range


of chemicals.

PACKAGING

Pieces per carton: 120 pcs Carton weight: 6.7 kg Cartons per pallet: 48 pcs Pieces per pallet: 5760 pcs

Pallet dimensions: 80 x 120 x 110 cm





NEUTRAL



APPLICATIONS

The **U-E20-FLEX** is a 2 mm damper. Placed on the **U-TOP-FLEX** support, it stabilises the paver, provides additional acoustic comfort, and compensates for variations in paver thickness.

SAFETY INSTRUCTIONS

Buzon pedestals and accessories are designed to support external raised floors for pedestrian traffic only and are not designed to support or be subjected to moving and/or vibrating machinery & equipment, including maintenance, cleaning vehicles, automobiles and other similar equipment.



043-055-1351

Buzon USA West Projects



References

- · Sun's Practice Facility Phoenix, AZ
- Sony Studio HQ Los Angeles, CA
- Apple Campus Palo Alto, CA
- Samsung HQ Palo Alto, CA
- Lucille Packard Children's Hospital Stanford, CA
- · Haas School of Business UC Berkeley, CA
- IMAX Theater Nassau, NY
- Four Seasons Hotel Honolulu, HI
- · Canal Street Rooftop Pool New Orleans, LA

- · Smith Center Harvard University Cambridge, MA
- · Microsoft Campus Redmond, WA
- · The Dean Palo Alto, CA
- · Nike Campus HQ Beaverton, OR
- · Hoakalei CC Ewa Beach, HI
- · Hilton Grand Islander Honolulu, HI
- Four Seasons Resort at Ko Olina Kapolei, HI
- One World Trade Center New York City, NY
- Wynn Resort & Casino Hotel Las Vegas, NV











(503) 954 - 3336